T7P Terminal

integrated POS terminal and printer from Hypercom

T7P Features:

Small footprint takes up less counter space

Easy-to-learn, simple-to-use 35-key keyboard

Fast transactions and authorizations

Clerk-friendly operations, easily changed paper and ribbons

Cashier-replaceable printer module

High visibility 2 x 20 backlit LCD display

Full Track I and 2 card reader standard

Field-proven, high reliability

Smart card reader option (T7PS), EMV-certified

The T7P is designed for upgrading authorizationonly equipment and for merchants moving
to data capture and debit applications. It
features an integrated modular impact
or quiet thermal printer. T7P can read
all types of credit, debit, check and
charge cards, and an external PIN
pad can be attached to support
cardholder entry of PIN numbers.
Dedicated function keys allow
one-step operation of everyday
processes.

Price/performance benefits of the T7P include savings on user training, reduced telephone line costs, and shorter processing and settlement times. The T7P also accommodates new software applications demanded by the marketplace which can be remotely developeded from a sophisticated

which can be remotely downloaded from a sophisticated Terminal Management System.







T7P Specifications

ISO 7816, EMV-certified

Display LCD 2 lines x 20

IC card interface

Backlight CCFL 25,000 hours to half-life

Card reader Magnetic stripe Track 1, 2 (Track 3 optional)

Reliability 400,000 reads

Smart card

reader

Keypad

Silicone rubber 35 keys
Reliability 350,000 operations

Comms Modem 2400 bps, I200 bps, synchronous (SDLC) and

asynchronous, 9600 bps optional

LAN RS485 Hypercom LAN

PIN pad port 2-wire or 4-wire, RS422

Peripheral S7C, S7SC, S8, P7E, ICE, HFT105

compatibility

Printer Type <u>Thermal</u> <u>Impact</u>

Columns 40 40

Paper roll width

2.26 in/57.5 mm,

Paper roll type

Single ply

MTBF

5 million lines

2.26 in/57.7 mm

1, 2, or 3-ply

1.35 million lines

Memory RAM Up to 1.0 MB

EPROM 32 KB

RAM backup 5-year battery

Power AC 85-250 V AC, 50/60 Hz

DC 24 V, IA

Environment Temperature 0-45 C/32-115 F

Humidity Max 85%, non-condensing

ESD 12,000 volts

Footprint Dimensions 6.25 in \times 11.5 in \times 4.5 in/15.88 cm \times 29.21 cm \times 11.43 cm

Weight 1.98 lbs/0.74 kg approximate weight

Reliability MTBF 100,000 hours (not including printer)

WORLD HEADQUARTERS/ NORTH AMERICA

Hypercom Corporation 2851 W. Kathleen Road Phoenix, Arizona 85053 USA

TEL: +1.602.504.5000 FAX: +1.602.504.4578

LATIN AMERICA

Hypercom Latin America Rua Joaquim Floriano 72 16° andar Cj161 04534-000 ItaimBibi São Paulo, Brazil TEL: +55.11.3365.2600 FAX: +55.11.3365.2610

ASIA/PACIFIC RIM

Hypercom Asia Ltd. 21/F Metro Centre II 21 Lam Hing Street Kowloon Bay Hong Kong TEL: +852.2561.6800 FAX: +852.2561.5890

EUROPE, MIDDLE EAST, AFRICA

Hypercom Europe Ltd. Unit 2, Woking Eight Forsyth Road Woking, GU21 5SB United Kingdom TEL: +44.1.483.718600 FAX: +44.1.483.718601



www.hypercom.com 1.877.840.9820

©2001 Hypercom Corporation, all rights reserved. Hypercom, the Hypercom logo and ICE-PAC are registered trademarks of Hypercom Corporation. The Global Leader in Electronic Transaction Solutions is a trademark of Hypercom Corporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Hypercom Corporation (NYSE:HYC) is a leading global provider of electronic payment solutions that add value at the point-of-sale for consumers, merchants and acquirers. Hypercom products include secure card payment terminals and web appliances, networking equipment and software applications for e-commerce, m-commerce, smart cards and traditional payment applications.

Headquartered in Phoenix, Arizona, Hypercom maintains an installed base of more than 3.5 million card payment terminals which operate in over 100 countries and conduct more than 2.5 billion transactions annually.

062-IA