

MTT 1500 Technical Specifications



Wireless Communications	Dual band GSM TM 850 / 1900 MHz (Siemens C56)
POS Memory	RAM for POS Applications 128 Kbyte SRAM 256 Kbytes Flash: 1 Megabyte available out of 4 Megabyte
POS Processor	High performance CPU 16 bit microprocessor optimized for low power consumption
SAMs	1 SAM Slot
Security	MULTOS 4.06+ Security Module PKI (for key exchange between MTT and Server) 3DES Encryption, RSA Encryption
Keypad	internal PINPAD option
Magnetic card reader	3 Track Reader
Smart Card reader	EMV Level1 EMV Level 2 Visa Smart POS integration in progress
Battery	Up to 200 hours stand-by time Up to 300 Transactions per charge
Dimensions	Height: 4" (102 mm) x Width: 2"8 (54 mm) x Depth: 1"3/16 (30 mm)
Weight	Total Weight: 120g POS plus 250g printer
Mobile Printer	Thermal printer Pocket size (75 x 103 * 34mm) Light weight (250g) for true mobility. High speed (50mm/sec) High-resolution (203dpi : 8dots/mm). Easier paper loading by clamshell design Supports text and graphic printing Serial(RS-232C), IrDA Ver 1.0(SIR) interface Battery duration: 1 hour continuous printing Rechargeable 7.2VDC 880mAH (Ni-MH)

WAY Systems licenses technology from:



For more information:
email us at info@waysystems.com
or visit us on the web at www.waysystems.com

WAY Systems, Inc.
200 Unicorn Park, Woburn, MA 01801 USA
+1 (781) 569-0420
sales@waysystems.com